



Providing Solutions in Pressure Sensitive Films

Product Construction Sheet

FLEX-Vu® OL 300 CLEAR VELVET L-29 142PolyC-9

GENERAL DESCRIPTION:

This is a clear velvet embossed polycarbonate film coated with a clear overlaminating pressure sensitive acrylic adhesive and backed with an ultra smooth super clear polyester release liner.

UL RECOGNITION:

This product is UL recognized for indoor use with occasional exposure to lubricating oil and water. For further information, please reference FLEXcon's UL file No MH10170 (N) or contact your FLEXcon Representative.

Table with 3 columns: PRODUCT DATA, VALUE, TEST METHOD. Rows include PHYSICAL PROPERTIES (Thickness, Adhesive, Liner) and Dimensional Stability (%).

ADHESION PROPERTIES\*\*

Table with 3 columns: Adhesion from (N/m), Average, TEST METHOD. Rows include Stainless Steel, Acrylic, Glass, Expected Shear (hours), and Tack (gm/sq cm).

\*\* For guidance only
This data is based on limited test results due to the custom nature of this product, not to be used for setting specifications.

Table with 2 columns: PROPERTY, VALUE. Rows include EXPECTED EXTERIOR LIFE, SERVICE TEMPERATURE RANGE, MINIMUM APPLICATION TEMPERATURE, and STORAGE STABILITY.

\* FLEX-Vu is a registered trademark of FLEXcon Company, Inc. 01-08-2006

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product.