

# 1007

## Production Information – December 2005

### Description

A low – density polythene based carpet and flooring protection tape coated with an emulsion acrylic adhesive system. Good resistance to moisture, sunlight and various climatic conditions. Designed for temporary protection only. Not to be left in situ for extended periods or subjected to repeated heavy traffic.

### Applications

- Needle Cord Carpets temporary protection (not for use on long pile surfaces)
- Can also be used to retain glass in damaged or shattered windows in auto and train salvage and building demolition operations.

### Technical Detail

Total Thickness		0.103mm
Backing Thickness		0.085mm
Tensile Strength	(Longitudinal)	23 n/mm
	(Transversal)	18 n/mm
Elongation	(Longitudinal)	310%
	(Transversal)	690%
Temperature		-10 to +60°C
Steel Adhesion		820g/25mm
Dielectric Strength		-
Colours	Clear	

### Note

Unless otherwise indicated, the figures above are average values and should not be treated at face value for specification purposes. The Company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British Standards, but other tolerances are available by request.