

Product Information

| Product Description

SH82

Skyrol [®] SH82 is an optically very clear polyester film. Both sides of the film are pretreated with an adhesion promoting coating. SH82 was developed as a substrate for printing labels, colour proofing, masking, overhead transparencies, engineering drawings, drafting and other items like these.

This grade is available in the thickness range from 50 to 250 microns.

| Typical Properties

Property	Unit	Value	Test Method
General			
Nominal Thickness	Gauge (μm)	200 50	SKC Method
Density	g/cm³	1.4	ASTM D 1505
Mechanical			
Tensile Strength	psi MD (Kg/mm²)	22 24	ASTM D 882
Elongation At Break	% MD TD	160 120	ASTM D 882
Friction Coefficient	μk µs	0.5 0.42	ASTM D 1894
Optical			
Haze	%	0.9	ASTM D 1003
Light Transmission	%	90	ASTM D 1003
Gloss	%	190	ASTM D 523
Thermal			
Heat Shrinkage	% MD TD	1.1 0.5	SKC Method (150°C x 30 min)

Unit Correlation : Gauge = $\mu m / 0.254$

psi = $Kg/mm^2 \times 1422.3$ N/mm² = $Kg/mm^2 \times 9.8$

This Information is the best currently available on the subject. The results should, however, only be regarded as a general guide to material properties and not as a guarantee. Some of the properties can be changed as a result of supplier's efforts to improve the quality or production efficiency of the subject.

I UK Agent, Distributor and Stockist for SKC

Graphic Image Films Ltd Unit 5, Ridge Way, Crendon Industrial Park, Long Crendon, Bucks, UK, HP18 9BF

Tel: 0044 (0) 1844 208308 Fax: 0044 (0) 1844208608 E-Mail: Info.gif@graphicimagefilms.co.uk Web: www.graphicimagefilms.co.uk