



SH82

Product Information

I Product Description

"Skyrol"[®] SH82 is an optically very clear, glossy film, with the ink/coating adhesion promotion pretreatment on both sides. This grade has been developed for use as a substrate for printing. Label, colour proofing, masking, overhead transparencies, engineering, drafting etc. This grade is available in the thickness range from 50 to 250 microns.

I Typical Properties

Property	Unit	Value	Test Method
General			
Nominal Thickness	Gauge (μm)	300 75	SKC Method
Density	g/cm^3	1.4	ASTM D 1505
Mechanical			
Tensile Strength	psi (Kg/mm^2)	MD 22 TD 22	ASTM D 882
Elongation At Break	%	MD 140 TD 100	ASTM D 882
Friction Coefficient	μk μs	0.46 0.42	ASTM D 1894
Optical			
Haze	%	1.1	ASTM D 1003
Light Transmission	%	93	ASTM D 1003
Gloss	%	185	ASTM D 523
Thermal			
Heat Shrinkage	%	MD 1.5 TD 0.5	SKC Method (150°C x 30 min)

Unit Correlation : Gauge = $\mu\text{m} / 0.254$
 psi = $\text{Kg/mm}^2 \times 1422.3$
 N/mm^2 = $\text{Kg/mm}^2 \times 9.8$

This Information is the best currently available on the subject. The results should, however, only be regarded as a general guide to material properties and not as a guarantee. Some of the properties can be changed as a result of supplier's efforts to improve the quality or production efficiency of the subject.

I UK Agent, Distributor and Stockist for SKC

Graphic Image Films Ltd
 Unit 5, Ridge Way,
 Crendon Industrial Park,
 Long Crendon, Bucks. HP18 9BF

Tel No: 0044 (0) 1844-208308
 Fax No: 0044 (0) 1844-208608
 E-Mail: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk