



Membrane Switch Spacer 7945MP

Product Data Sheet

Updated : April 2004
Supersedes : July 2000

Physical Properties

Not for specification purposes

Liner	58# Polycoated Kraft
Adhesive	2.0 thou #200 "High Performance" Acrylic
Carrier	1.0 thou Transparent Polyester
Shelf Life	12 months from date of manufacture by 3M if stored at room temperature condition in cool, dry and sun protected room.

Features:

- High performance adhesive withstands repeated stresses from switch activation.
- Excellent shear strength.
- Long term, environmentally stable adhesive to resist UV light, chemicals and temperatures to 300°F
- Moisture stable liner
- Liner is silicone coated on adhesive side only, allowing for ease of stacking parts.

Applications

- Designed to separate circuitry until actuation.

Physical Properties

Not for specification purposes

Initial Adhesion, dynamic peel 90° to stainless steel, 2 mil aluminium backing.
(modified ASTM D-3330)

6.1 N/10mm

Date : April 2004
 Membrane Spacer
 7945MP

Processing

Die Cutting:

Use sharp tooling, properly designed for the cutting of pressure sensitive adhesives and the laminating material. It is helpful to lubricate tooling with a low residue vanishing type of oil for improved handling. Consult the manufacturers Material Safety Data Sheet for proper storage and handling of vanishing oils.

Roll Laminating:

Use rubber over steel roll set up with firm application pressure. Make adhesive to substrate contact at nip area only to exclude air entrapment.

Special Considerations

For maximum bond strength, surface should be thoroughly cleaned and dried. a typical cleaning solvent is heptane or isopropyl alcohol. Consult the manufacturers Material Safety Data Sheet for proper handling and storage instructions.

Bond strength may be improved with firm application pressure and moderate heat, which will help adhesive flow out and develop better contact with bonding surface.

3M is a trademark of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Tapes & Adhesives Group

© 3M United Kingdom PLC 2004

3M United Kingdom PLC
 3M Centre
 Cain Road,
 Bracknell, Berkshire,
 RG12 8HT

Product Information :
 Tel 0870 60 800 50
 Fax 0870 60 700 99

3M Ireland
 3M House, Adelphi Centre,
 Upper Georges Street,
 Dun Laoghaire, Co. Dublin,
 Ireland

Customer Service :
 Tel (01) 280 3555
 Fax (01) 280 3509