



Providing Solutions in Pressure Sensitive Films

Product Construction Sheet

FLEXmark® PM 200 CLEAR TC-200 L-46 98PFW

GENERAL DESCRIPTION:

This is a topcoated clear polyester film coated with a permanent pressure sensitive acrylic adhesive and backed with a two side poly coated lay flat release liner.

UL RECOGNITION:

This product is UL recognized for indoor/outdoor use with occasional exposure to lubricating oil and Water. For further information, please reference FLEXcons` UL file No MH10170 (N) or contact your FLEXcon Representative.

Table with 3 columns: PRODUCT DATA, VALUE, TEST METHOD. Rows include PHYSICAL PROPERTIES, Thickness (micron), Dimensional Stability (%).

ADHESION PROPERTIES** - THIS DATA IS BASED ON LIMITED TEST RESULTS DUE TO THE CUSTOM NATURE OF THIS PRODUCT.

Table with 3 columns: Adhesion from, Average N/m, TEST METHOD. Rows include Stainless Steel, Acrylic, Glass, Expected Shear (hours), Tack (gm/sq cm).

** For guidance only, not to be used for setting specifications. All data are based on three production runs.

Table with 2 columns: PROPERTY, VALUE. Rows include EXPECTED EXTERIOR LIFE, SERVICE TEMPERATURE RANGE, MINIMUM APPLICATION TEMPERATURE, STORAGE STABILITY.

* FLEXmark is a registered trademark of FLEXcon Company, Inc. 08/09/2003

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product.