



Providing Solutions in Pressure Sensitive Films

Product Construction Sheet

FLEXmark® PM 200 CLEAR TC-200 L-46 98PFW

GENERAL DESCRIPTION:

This is a topcoated clear polyester film coated with a permanent pressure sensitive acrylic adhesive and backed with a two side poly coated lay flat release liner.

UL RECOGNITION:

This product is UL recognized for indoor/outdoor use with occasional exposure to lubricating oil and Water. For further information, please reference FLEXcons` UL file No MH10170 (N) or contact your FLEXcon Representative.

PRODUCT DATA	VALUE	TEST METHOD
PHYSICAL PROPERTIES		
Thickness (micron)	Film: 50	+/- 10 %
	Adhesive: 25-28	+/- 3
	Liner: 166	+/- 10 %
Dimensional Stability (%)	No shrinkage observed	On Al panel at 160`F (71`C) for 24 hr.

ADHESION PROPERTIES** - THIS DATA IS BASED ON LIMITED TEST RESULTS DUE TO THE CUSTOM NATURE OF THIS PRODUCT.

Adhesion from	Average N/m	
Stainless Steel	726	PSTC 1 (Modified for 72 hr dwell time)
Acrylic	737	
Glass	682	
Expected Shear (hours)	25	FTM 8
Tack (gm/sq cm)	370	ASTM D 2979

** For guidance only, not to be used for setting specifications. All data are based on three production runs.

EXPECTED EXTERIOR LIFE	Two years
SERVICE TEMPERATURE RANGE	-40`C to 150`C
MINIMUM APPLICATION TEMPERATURE	10`C
STORAGE STABILITY	Two years stored at 21`C and 50% RH

* FLEXmark is a registered trademark of FLEXcon Company, Inc.

08/09/2003

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.